PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package | Pins	Package qty | Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
5962-0254601VPA	Active	Production	CDIP (NAB) | 8	40 | TUBE	No	SNPB	Level-1-NA-UNLIM	-55 to 125	LMH6702J-QV 5962-02546 01VPA Q ACO 01VPA Q >T
5962-0254601VZA	Active	Production	CFP (NAC) | 10	54 | JEDEC TRAY (5+1)	No	SNPB	Level-1-NA-UNLIM	-55 to 125	LMH6702 WGQMLV Q 5962-02546 01VZA ACO 01VZA >T
5962F0254601VPA	Active	Production	CDIP (NAB) | 8	40 | TUBE	No	SNPB	Level-1-NA-UNLIM	-55 to 125	LMH6702JFQV 5962F02546 01VPA Q ACO 01VPA Q >T
5962F0254601VZA	Active	Production	CFP (NAC) | 10	54 | JEDEC TRAY (5+1)	No	SNPB	Level-1-NA-UNLIM	-55 to 125	LMH6702 WGFQMLV Q 5962F02546 01VZA ACO 01VZA >T
5962F0254602VPA	Active	Production	CDIP (NAB) | 8	40 | TUBE	No	SNPB	Level-1-NA-UNLIM	-55 to 125	LMH6702JFLQV 5962F02546 02VPA Q ACO 02VPA Q >T
LMH6702J-QMLV	Active	Production	CDIP (NAB) | 8	40 | TUBE	No	SNPB	Level-1-NA-UNLIM	-55 to 125	LMH6702J-QV 5962-02546 01VPA Q ACO 01VPA Q >T
LMH6702J-QMLV.A	Active	Production	CDIP (NAB) | 8	40 | TUBE	No	SNPB	Level-1-NA-UNLIM	-55 to 125	LMH6702J-QV 5962-02546 01VPA Q ACO 01VPA Q >T
LMH6702JFLQMLV	Active	Production	CDIP (NAB) | 8	40 | TUBE	No	SNPB	Level-1-NA-UNLIM	-55 to 125	LMH6702JFLQV 5962F02546 02VPA Q ACO 02VPA Q >T

Orderable part number	Status (1)	Material type (2)	Package | Pins	Package qty | Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
LMH6702JFQMLV	Active	Production	CDIP (NAB) | 8	40 | TUBE	No	SNPB	Level-1-NA-UNLIM	-55 to 125	LMH6702JFQV 5962F02546 01VPA Q ACO 01VPA Q >T
LMH6702JFQMLV.A	Active	Production	CDIP (NAB) | 8	40 | TUBE	No	SNPB	Level-1-NA-UNLIM	-55 to 125	LMH6702JFQV 5962F02546 01VPA Q ACO 01VPA Q >T
LMH6702WG-QMLV	Active	Production	CFP (NAC) | 10	54 | JEDEC TRAY (5+1)	No	SNPB	Level-1-NA-UNLIM	-55 to 125	LMH6702 WGQMLV Q 5962-02546 01VZA ACO 01VZA >T
LMH6702WG-QMLV.A	Active	Production	CFP (NAC) | 10	54 | JEDEC TRAY (5+1)	No	SNPB	Level-1-NA-UNLIM	-55 to 125	LMH6702 WGQMLV Q 5962-02546 01VZA ACO 01VZA >T
LMH6702WGFQMLV	Active	Production	CFP (NAC) | 10	54 | JEDEC TRAY (5+1)	No	SNPB	Level-1-NA-UNLIM	-55 to 125	LMH6702 WGFQMLV Q 5962F02546 01VZA ACO 01VZA >T
LMH6702WGFQMLV.A	Active	Production	CFP (NAC) | 10	54 | JEDEC TRAY (5+1)	No	SNPB	Level-1-NA-UNLIM	-55 to 125	LMH6702 WGFQMLV Q 5962F02546 01VZA ACO 01VZA >T

(1) **Status:** For more details on status, see our product life cycle.

(2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

(3) **RoHS values:** Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

(4) Lead finish/Ball material: Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) MSL rating/Peak reflow: The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

(6) Part marking: There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.